


TP-N : POMPE IN-LINE SIMPLE POUR EAU CHAUDE SANITAIRE

Matériau :	Acier inoxydable
Température du liquide :	de -25°C à +120 °C max.
Pression de service maxi :	10 bar
Indice de protection :	IP 55
Classe d'isolation :	F
Tension :	1~ : 1 x 220-240 V - 3~ : 3 x 220-240D/380-415V
Garniture mécanique :	BQQE




Raccord	Entraxe [mm]	P2 [kW]	In [A]	PN [bar]	Type	Code Art.
1 ~						
G 1½	180	0.12	1.36-1.57	10	TP 25-50/2	98346632
		0.18	1.52-1.65	10	TP 25-80/2	98282100
G 2	180	0.12	1.36-1.57	10	TP 32-50/2	98282162
		0.25	1.75-2.04	10	TP 32-80/2	98346642
		0.37	2.95/2.70	10	TP 32-90/2	98282352
DN 40	250	0.12	1.36-1.57	6/10	TP 40-50/2	98282357
		0.25	1.75-2.04	6/10	TP 40-80/2	98346645
3 ~						
G 1½	180	0.12	0.59/0.34	10	TP 25-50/2	98346612
		0.18	0.90/0.52	10	TP 25-80/2	98346639
G 2	180	0.12	0.59/0.34	10	TP 32-50/2	98346615
		0.25	1.63/0.94	10	TP 32-80/2	98346623
		0.37	1.74/1.00	10	TP 32-90/2	98346629
DN 40	250	0.12	0.59/0.34	6/10	TP 40-50/2	98346618
		0.25	1.63/0.94	6/10	TP 40-80/2	98346626

JEU DE 2 RACCORDS-UNIONS



Pos.	Raccord	Matériau	PN [bar]	Code Art.
a	G 1½ / Rp 1	Laiton/Bronze	10	529972

JEU DE 2 RACCORDS-UNIONS AVEC VANNE



Pos.	Raccord	Matériau	PN [bar]	Code Art.
b	G 1½ / Rp 1	Laiton/Bronze	10	519806
b	G 2 / Rp 1½	Laiton	10	505539

