

SP-NE : POMPES IMMERGÉES 4"/6" EN INOX AISI 316

Température du liquide : max. +40 °C
 Indice de protection : IP68
 Moteur : En acier inox AISI 904L
 Tension d'alimentation : 3x380-415 V



MPG 16

Raccord	Diam. Mot.	P2 [kW]	In [A]	Tempcon	Clapet anti-retour	Type	Code Art.	
Rp 1½	4"	0.75	1.92-1.84-1.84	•		SP 3A-6NE	10221906	
		0.75	1.92-1.84-1.84	•		SP 3A-9NE	10221909	
		0.75	1.92-1.84-1.84	•		SP 3A-12NE	10221912	
		1.10	2.80-2.75-2.75	•		SP 3A-15NE	10221915	
		1.10	2.80-2.75-2.75	•		SP 3A-18NE	10221918	
		1.50	3.95-4.00-4.10	•		SP 3A-22NE	10221922	
		1.50	3.95-4.00-4.10	•		SP 3A-25NE	10221925	
		2.20	5.75-6.00-6.30	•		SP 3A-29NE	10221929	
Rp 1½	4"	0.75	1.92-1.84-1.84	•		SP 5A-4NE	5221904	
		0.75	1.92-1.84-1.84	•		SP 5A-6NE	5221906	
		0.75	1.92-1.84-1.84	•		SP 5A-8NE	5221908	
		1.10	2.80-2.75-2.75	•		SP 5A-12NE	5221912	
		1.50	3.95-4.00-4.10	•		SP 5A-17NE	5221917	
		2.20	5.75-6.00-6.30	•		SP 5A-21NE	5221921	
		2.20	5.75-6.00-6.30	•		SP 5A-25NE	5221925	
		3.00	7.70-7.85-8.10	•		SP 5A-33NE	5221933	
Rp 2	4"	0.75	1.92-1.84-1.84		•	SP 9-4NE	98780182	
		1.10	2.80-2.75-2.75		•	SP 9-5NE	98730819	
		1.50	3.95-4.00-4.10		•	SP 9-8NE	98730820	
		2.20	5.75-6.00-6.30		•	SP 9-10NE	98779812	
		2.20	5.75-6.00-6.30		•	SP 9-11NE	98730831	
		3.00	7.70-7.85-8.10		•	SP 9-13NE	98730832	
		3.00	7.70-7.85-8.10		•	SP 9-16NE	98730834	
		4.00	9.75-9.60-9.80		•	SP 9-18NE	98730835	
		4.00	9.75-9.60-9.80		•	SP 9-21NE	98730836	

MPG 17

Raccord	Diam. Mot.	P2 [kW]	In [A]	Tempcon	Clapet anti-retour	Type	Code Art.	
Rp 2 ½	4"	0.75	1.92-1.84-1.84	•		SP 17-1NE	12C91901	
		1.10	2.80-2.75-2.75	•		SP 17-2NE	12C91902	
		2.20	5.75-6.00-6.30	•		SP 17-3NE	12C91903	
		2.20	5.75-6.00-6.30	•		SP 17-4NE	12C91904	
		3.00	7.70-7.85-8.10	•		SP 17-5NE	12C91905	
		4.00	9.75-9.60-9.80	•		SP 17-6NE	12C91906	
		4.00	9.75-9.60-9.80	•		SP 17-7NE	12C91907	
		5.50	13.0-13.0-13.4	•		SP 17-8NE	12C91908	
		5.50	13.0-13.0-13.4	•		SP 17-9NE	12C91909	
		5.50	13.0-13.0-13.4	•		SP 17-10NE	12C91910	







