

Camlock

MIL C-27487

MATERIAL MATIÈRE MATERIAL

AL = Aluminium

BR = Brass Laiton Latón

SS = Stainless steel Inox

PP = Polypropylene

On request Sur demande Bajo pedido

SIZE DIMENSIONS DIMENSIONES

From DN 1/2" to DN 6"


THREAD FILETAGE ROSCA

BSPP/NF ISO 228-1


GASKETS JOINTS JUNTA

NBR


COUPLER




TYPE B Male



TYPE C Hose shank




TYPE D Female




TYPE DC Dust plug

DN mm	B
15	32
20	42
25	46
32	56
40	64
50	76
65	87
80	103
100	132
125	162
150	194


ADAPTER




TYPE A Female



TYPE E Hose shank



TYPE F Male



TYPE DP Dust plug

DN mm	E
15	23,8
20	32,1
25	36,7
32	45,5
40	53,4
50	63
65	75,8
80	91,5
100	119,5
125	146
150	175,9

AL = Aluminium
BR = Brass *Laiton Latón*
ST = Steel *Acier Acero*
SS = Stainless steel *Inox*
PP = Polypropylene

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.
 Type A. Type A. <i>Tipo A.</i>	AL	1/2"		510 16 50
		3/4"		510 16 51
		1"		510 16 52
		1"1/4		510 16 53
		1"1/2		510 16 54
		2"		510 16 55
		2"1/2		510 16 56
		3"		510 16 57
		4"		510 16 58
		5"		510 16 59
		6"		510 16 60
 Type B. Type B. <i>Tipo B.</i>	AL	1/2"		510 16 61
		3/4"		510 16 62
		1"		510 16 63
		1"1/4		510 16 64
		1"1/2		510 16 65
		2"		510 16 66
		2"1/2		510 16 67
		3"		510 16 68
		4"		510 16 69
		5"		510 16 70
		6"		510 16 71
 Type C. Type C. <i>Tipo C.</i>	AL	1/2"		510 16 72
		3/4"		510 16 73
		1"		510 16 74
		1"1/4		510 16 75
		1"1/2		510 16 76
		2"		510 16 77
		2"1/2		510 16 78
		3"		510 16 79
		4"		510 16 80
		5"		510 16 81
		6"		510 16 82
 Type D. Type D. <i>Tipo D.</i>	AL	1/2"		510 16 83
		3/4"		510 16 84
		1"		510 16 85
		1"1/4		510 16 86
		1"1/2		510 16 87
		2"		510 16 88
		2"1/2		510 16 89
		3"		510 16 90
		4"		510 16 91
		5"		510 16 92
		6"		510 16 93

AL = Aluminium
 BR = Brass **Laiton Latón**
 ST = Steel **Acier Acero**
 SS = Stainless steel **Inox**
 PP = Polypropylene

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.
 Type E. Type E. Tipo E.	AL	1/2"		510 16 94
		3/4"		510 16 95
		1"		510 16 96
		1"1/4		510 16 97
		1"1/2		510 16 98
		2"		510 16 99
		2"1/2		510 17 00
		3"		510 17 01
		4"		510 17 02
		5"		510 17 03
		6"		510 17 04
 Type F. Type F. Tipo F.	AL	1/2"		510 17 05
		3/4"		510 17 06
		1"		510 17 07
		1"1/4		510 17 08
		1"1/2		510 17 09
		2"		510 17 10
		2"1/2		510 17 11
		3"		510 17 12
		4"		510 17 13
		5"		510 17 14
		6"		510 17 15
 Type DC. Type DC. Tipo DC.	AL	1/2"		510 17 16
		3/4"		510 17 17
		1"		510 17 18
		1"1/4		510 17 19
		1"1/2		510 17 20
		2"		510 17 21
		2"1/2		510 17 22
		3"		510 17 23
		4"		510 17 24
		5"		510 17 25
		6"		510 17 26
 Type DP. Type DP. Tipo DP.	AL	1/2"		510 17 27
		3/4"		510 17 28
		1"		510 17 29
		1"1/4		510 17 30
		1"1/2		510 17 31
		2"		510 17 32
		2"1/2		510 17 33
		3"		510 17 34
		4"		510 17 35
		5"		510 17 36
		6"		510 17 37

AL = Aluminium
BR = Brass *Laiton Latón*
ST = Steel *Acier Acero*
SS = Stainless steel *Inox*
PP = Polypropylene

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.
 Type A. Type A. <i>Tipo A.</i>	SS 316	1/2"		510 13 96
		3/4"		510 13 97
		1"		510 13 98
		1"1/4		510 13 99
		1"1/2		510 14 00
		2"		510 14 01
		2"1/2		510 14 02
		3"		510 14 03
		4"		510 14 04
		5"		510 15 87
		6"		510 14 05
 Type B. Type B. <i>Tipo B.</i>	SS 316	1/2"		510 14 26
		3/4"		510 14 27
		1"		510 14 28
		1"1/4		510 14 29
		1"1/2		510 14 30
		2"		510 14 31
		2"1/2		510 14 32
		3"		510 14 33
		4"		510 14 34
		5"		510 15 90
		6"		510 14 35
 Type C. Type C. <i>Tipo C.</i>	SS 316	1/2"		011 74 30
		3/4"		011 74 31
		1"		011 74 32
		1"1/4		011 74 33
		1"1/2		011 74 34
		2"		011 74 35
		2"1/2		011 74 36
		3"		011 74 37
		4"		011 74 38
		5"		510 15 85
		6"		510 13 94
 Type D. Type D. <i>Tipo D.</i>	SS 316	1/2"		510 14 16
		3/4"		510 14 17
		1"		510 14 18
		1"1/4		510 14 19
		1"1/2		510 14 20
		2"		510 14 21
		2"1/2		510 14 22
		3"		510 14 23
		4"		510 14 24
		5"		510 15 89
		6"		510 14 25

AL = Aluminium
BR = Brass Laiton Latón
ST = Steel Acier Acero
SS = Stainless steel Inox
PP = Polypropylene

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.
 Secure type D DIN 2828. Type D sécurisé DIN 2828. <i>Tipo D securizado DIN 2828.</i>	SS 316	3/4"		SAFD19
		1"		SAFD25
		1"1/4		SAFD32
		1"1/2		SAFD40
		2"		SAFD50
		2"1/2		SAFD65
		3"		SAFD80
		4"		SAFD100
 Type E. Type E. Tipo E.	SS 316	1/2"		011 74 43
		3/4"		011 74 44
		1"		011 74 45
		1"1/4		011 74 46
		1"1/2		011 74 47
		2"		011 74 48
		2"1/2		011 74 49
		3"		011 74 50
		4"		011 74 51
 Type F. Type F. Tipo F.	SS 316	5"		510 15 86
		6"		510 13 95
		1/2"		510 14 06
		3/4"		510 14 07
		1"1/4		510 14 09
		2"		510 14 11
		3"		510 14 13
		5"		510 15 88
		1"		510 14 08
		1"1/2		510 14 10
 Adaptor BW. Adapteur BW. <i>Adaptor BW.</i>	SS 316	2"1/2		510 14 12
		4"		510 14 14
		6"		510 14 15
		1/2"	21,3	510 20 11
		3/4"	26,9	510 20 12
		1"	33,7	510 20 13
		1"1/4	42,2	510 20 14
		1"1/2	48,3	510 20 15
		2"	60,3	510 20 16
		2"1/2	76,1	510 20 17
		3"	88,9	510 20 18
		4"	114,3	510 20 19
		5"	139,7	510 69 97

AL = Aluminium
BR = Brass *Laiton Latón*
ST = Steel *Acier Acero*
SS = Stainless steel *Inox*
PP = Polypropylene

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.
 Coupler BW. Coupleur BW. <i>Acoplador BW.</i>	SS 316	1/2"	21,3	510 20 20
		3/4"	26,9	510 20 21
		1"	33,7	510 20 22
		1"1/4	42,2	510 20 23
		1"1/2	48,3	510 20 24
		2"	60,3	510 20 25
		2"1/2	76,1	510 20 26
		3"	88,9	510 20 27
		4"	114,3	510 20 28
		5"	139,7	510 69 96
 Secure coupler BW. Coupleur BW sécurisé. <i>Acoplador securizado BW.</i>	SS 316	3/4"	26,7	SAFBW19
		1"	33,7	SAFBW25
		1"1/4	42,2	SAFBW32
		1"1/2	48,3	SAFBW40
		2"	60,3	SAFBW50
		2"1/2	76,1	SAFBW65
		3"	88,9	SAFBW80
 Type DC. Type DC. <i>Tipo DC.</i>	SS 316	1/2"		510 14 46
		3/4"		510 14 47
		1"		510 14 48
		1"1/2		510 14 50
		1"1/4		510 14 49
		2"		510 14 51
		2"1/2		510 14 52
		3"		510 14 53
		4"		510 14 54
		5"		510 15 92
 Type DP. Type DP. <i>Tipo DP.</i>	SS 316	6"		510 14 55
		1/2"		510 14 36
		3/4"		510 14 37
		1"		510 14 38
		1"1/4		510 14 39
		1"1/2		510 14 40
		2"		510 14 41
		2"1/2		510 14 42
		3"		510 14 43
		4"		510 14 44
		5"		510 15 91
		6"		510 14 45

AL = Aluminium
BR = Brass *Laiton Latón*
ST = Steel *Acier Acero*
SS = Stainless steel *Inox*
PP = Polypropylene

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.
 Type A. Type A. <i>Tipo A.</i>	BR	1/2"		510 20 81
		3/4"		510 20 82
		1"		510 20 83
		1"1/4		510 20 84
		1"1/2		510 20 85
		2"		510 20 86
		2"1/2		510 20 87
		3"		510 20 88
		4"		510 20 89
 Type B. Type B. <i>Tipo B.</i>	BR	1/2"		510 20 92
		3/4"		510 20 93
		1"		510 20 94
		1"1/4		510 20 95
		1"1/2		510 20 96
		2"		510 20 97
		2"1/2		510 20 98
		3"		510 20 99
		4"		510 21 00
 Type C. Type C. <i>Tipo C.</i>	BR	1/2"		510 21 03
		3/4"		510 21 04
		1"		510 21 05
		1"1/4		510 21 06
		1"1/2		510 21 07
		2"		510 21 08
		2"1/2		510 21 09
		3"		510 21 10
		4"		510 21 11
 Type D. Type D. <i>Tipo D.</i>	BR	1/2"		510 21 14
		3/4"		510 21 15
		1"		510 21 16
		1"1/4		510 21 17
		1"1/2		510 21 18
		2"		510 21 19
		2"1/2		510 21 20
		3"		510 21 21
		4"		510 21 22
 Type E. Type E. <i>Tipo E.</i>	BR	1/2"		510 21 25
		3/4"		510 21 26
		1"		510 21 27
		1"1/4		510 21 28
		1"1/2		510 21 29
		2"		510 21 30
		2"1/2		510 21 31
		3"		510 21 32
		4"		510 21 33

AL = Aluminium
BR = Brass *Laiton Latón*
ST = Steel *Acier Acero*
SS = Stainless steel *Inox*
PP = Polypropylene

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.
 Type F. Type F. <i>Tipo F.</i>	BR	1/2"		510 21 36
		3/4"		510 21 37
		1"		510 21 38
		1"1/4		510 21 39
		1"1/2		510 21 40
		2"		510 21 41
		2"1/2		510 21 42
		3"		510 21 43
		4"		510 21 44
 Type DC. Type DC. <i>Tipo DC.</i>	BR	1/2"		510 21 47
		3/4"		510 21 48
		1"		510 21 49
		1"1/4		510 21 50
		1"1/2		510 21 51
		2"		510 21 52
		2"1/2		510 21 53
		3"		510 21 54
 Type DP. Type DP. <i>Tipo DP.</i>	BR	1/2"		510 21 58
		3/4"		510 21 59
		1"		510 21 60
		1"1/4		510 21 61
		1"1/2		510 21 62
		2"		510 21 63
		2"1/2		510 21 64
		3"		510 21 65
 Pin. Epingle. <i>Pinza.</i>	SS 304	1/2" - 1"1/4		510 50 03
		1"1/2 - 6"		510 50 04
 Pack Handle/Ping/Ring. Pack Goupille/Anneau/Axe. <i>Pack Clavija/Eje/Anillo.</i>	SS 304	15 - 20		510 22 43
		25		510 22 44
		32 - 65		510 22 45
		80 - 125		510 22 46
		150		510 22 47

AL = Aluminium
 BR = Brass **Laiton Latón**
 ST = Steel **Acier Acero**
 SS = Stainless steel **Inox**
 PP = Polypropylene

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.
 Gasket. Joint. <i>Junta.</i>	NBR	1/2"		510 14 56
		3/4"		510 14 57
		1"		510 14 58
		1"1/4		510 14 59
		1"1/2		510 14 60
		2"		510 14 61
		2"1/2		510 14 62
		3"		510 14 63
		4"		510 14 64
		5"		510 20 00
 Gasket. Joint. <i>Junta.</i>	EPDM	6"		510 14 65
		1/2"		510 22 81
		3/4"		510 22 82
		1"		510 22 83
		1"1/4		510 22 84
		1"1/2		510 22 85
		2"		510 22 86
		2"1/2		510 22 87
		3"		510 22 88
		4"		510 22 89
 Gasket. Joint. <i>Junta.</i>	FPM	5"		510 22 90
		6"		510 22 91
		1/2"		510 14 66
		3/4"		510 14 67
		1"		510 14 68
		1"1/4		510 14 69
		1"1/2		510 14 70
		2"		510 14 71
		2"1/2		510 14 72
		3"		510 14 73
 Gasket. Joint. <i>Junta.</i>	FEP /Sili- cone	4"		510 14 74
		5"		510 22 80
		6"		510 14 75
		1/2"		510 14 94
		3/4"		510 14 95
		1"		510 14 96
		1"1/4		510 14 97
		1"1/2		510 14 98
		2"		510 14 99
		2"1/2		510 15 00
 Gasket. Joint. <i>Junta.</i>	FPM/ PFTE	3"		510 15 01
		4"		510 15 02
		1/2"		510 14 85
		3/4"		510 14 86
		1"		510 14 87
		1"1/4		510 14 88
		1"1/2		510 14 89
		2"		510 14 90
		2"1/2		510 14 91
		3"		510 14 92
		4"		510 14 93

Secure Camlock

MIL C-27487

MATERIAL MATIÈRE MATERIAL

 SS = Stainless steel  Inox

SIZE DIMENSIONS DIMENSIONES

From DN 3/4" to DN 4"


THREAD FILETAGE ROSCA

BSPP/NF ISO 228-1


GASKETS JOINTS JUNTA

NBR


COUPLER



TYPE BW



TYPE DL Smooth shank



TYPE D Female

DN mm	B
15	32
20	42
25	46
32	56
40	64
50	76
65	87
80	103
100	132
125	162
150	194



AL = Aluminium BR = Brass Laiton Latón ST = Steel Acier Acero SS = Stainless steel Inox PP = Polypropylene

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.
 Coupler BW. Coupleur BW. <i>Acoplador BW.</i>	SS 316	3/4"	26,7	SAFBW19
		1"	33,7	SAFBW25
		1"1/4	42,2	SAFBW32
		1"1/2	48,3	SAFBW40
		2"	60,3	SAFBW50
		2"1/2	76,1	SAFBW65
		3"	88,9	SAFBW80
		4"	114,3	SAFBW100
 Secure type C with smooth shank DIN 2817. Type C douille lisse DIN 2817. <i>Tipo C caña lisa DIN 2817.</i>	SS 316	3/4"		SAFDL19
		1"		SAFDL25
		1"1/4		SAFDL32
		1"1/2		SAFDL40
		2"		SAFDL50
		2"1/2		SAFDL65
		3"		SAFDL80
		4"		SAFDL100
 Secure type D DIN 2828. Type D DIN 2828. <i>Tipo D DIN 2828.</i>	SS 316	3/4"		SAFD19
		1"		SAFD25
		1"1/4		SAFD32
		1"1/2		SAFD40
		2"		SAFD50
		2"1/2		SAFD65
		3"		SAFD80
		4"		SAFD100